

# Makara

## SERI TEKNOLOGI

Improved Predictive Power Control of CDMA System in Rayleigh Fading Channel

Kinerja Skema Pemberian Tanda Air Video Digital Berbasis DWT-SVD dengan Detektor Semi-Blind

Penerapan Kamera Web Sebagai Pendeteksi Gerakan dengan Antar Muka *Directshow*

Stabilitas Termal Galeri *Clay* pada Komposit Nano Polipropilena-Clay Montmorillonit dengan Pengkompatibel Polipropilena-g-Maleik Anhidrida

Induksi dan Konduksi Gelombang Elektromagnetik Akibat Sambaran Petir pada Jaringan Tegangan Rendah

Environmental Remediation Full-Scale Implementation: Back To Simple Microbial Massive Culture Approaches

Penetapan Rute dan Perhitungan Keekonomian Pipa Transmisi Gas Muara Bekasi - Muara Tawar Melalui Jalur Lepas Pantai

Pembuatan Nanopartikel Emas Radioaktif dengan Aktivasi Neutron

Lipid Production from Microalgae *Chlorella vulgaris* as a Promising Candidate for Biodiesel Production

## **DEWAN REDAKSI**

### **Jurnal Makara Seri Teknologi**

**Pengarah:**  
Bachtiar Alam  
Budiarso

**Pemimpin Umum:**  
Yoki Yulizar

**Ketua Editor:**  
Misri Gozan

**Dewan Editor:**

Bambang Prasetya (LIPI)  
Raldi Artono Koestoer (UI)  
Haryodwito Armono (ITS)  
Mukhtasor (ITS)  
Nurul Taufiqurrahman (LIPI)  
Siti Syamsiah (UGM)

Siswa Setyahadi (BPPT)  
Kalamullah Ramli (UI)  
Kemas Ridwan (UI)  
Slamet (UI)  
Sri Harjanto (UI)  
Titiresmi (BPPT)

**Editor Pelaksana:**  
Fuad Gani  
Mukhlis Sutami

**Administrasi:**  
Vera Andriyani, Cucu Sukaesih, Indah Ayu Permata Sary

**Kantor Editor:**  
Gedung DRPM-UI, Kampus Universitas Indonesia, Depok 16424 - Indonesia  
Telp.+62 21 7270152; 78849118 Fax.+62 21 78849119  
Homepage: <http://journal.ui.ac.id>  
E-mail: [editor\\_makara@ui.ac.id](mailto:editor_makara@ui.ac.id); [editor\\_makara@yahoo.com](mailto:editor_makara@yahoo.com)

MAKARA Seri TEKNOLOGI merupakan jurnal ilmiah yang menyajikan artikel orisinal tentang pengetahuan dan informasi riset atau aplikasi riset dan pengembangan terkini dalam bidang teknologi. Jurnal ini merupakan sarana publikasi dan ajang berbagi karya riset dan pengembangannya di bidang teknologi. Pemuatan artikel di jurnal ini dialamatkan ke kantor editor. Informasi lengkap untuk pemuatan artikel dan petunjuk penulisan artikel tersedia di dalam setiap terbitan. Artikel yang masuk akan melalui proses seleksi mitra bestari dan/atau editor. Jurnal ini terbit secara berkala sebanyak dua kali dalam setahun (April dan November). Pemuatan naskah tidak dipungut biaya. MAKARA Seri TEKNOLOGI adalah peningkatan dari MAKARA Seri B: Bidang Sains dan Teknologi sebagai penyempurnaan dari Jurnal Penelitian Universitas Indonesia MAKARA yang terbit sejak Januari 1997.

MAKARA Seri TEKNOLOGI is a scientific journal publishing original papers on new knowledge and information in research or applied research and development in technology. The journal provides a broad-based forum for the publication and sharing of ongoing research and development efforts in technology. Submission of the article on this journal is addressed to editorial office. Detailed information on how to submit the article and the writing instruction to authors are available on the inside of every edition. All articles will be subjected to peer and/or editorial review. The journal is published two times a year (April and November). No page charges for submission. MAKARA Seri TEKNOLOGI is an elaboration of MAKARA Seri B: Sains dan Teknologi that was the improvement of Jurnal Penelitian Universitas Indonesia MAKARA that published since January 1997.

Mengutip ringkasan dan pernyataan atau mencetak ulang gambar atau tabel dari jurnal ini harus mendapat ijin langsung dari penulis. Produksi ulang dalam bentuk kumpulan cetakan ulang atau untuk kepentingan periklanan atau promosi atau publikasi ulang dalam bentuk apapun harus seijin salah satu penulis dan mendapat lisensi dari penerbit. Jurnal ini didedarkan sebagai tukaran untuk perguruan tinggi, lembaga penelitian dan perpustakaan di dalam dan luar negeri. Hanya iklan menyangkut teknologi dan produk yang berhubungan dengannya yang dapat dimuat pada jurnal ini.

Permission to quote excerpts and statements or reprint any figures or tables in this journal should be obtained directly from the authors. Reproduction in a reprint collection or for advertising or promotional purposes or republication in any form requires permission of one of the authors and a licence from the publisher. This journal is distributed for national and regional higher institution, institutional research and libraries. Only advertisements of technology or related products will be allowed space in this journal.

## EDITORIAL

Salah satu wujud syukur ke hadirat Illahi dari bangsa Indonesia adalah adanya semangat yang tinggi dalam mengembangkan Ilmu Pengetahuan dan Teknologi. Kita melihat peningkatan signifikan dana Departemen Pendidikan Nasional untuk penelitian di perguruan tinggi di tahun 2009 ini. Jumlah proposal yang masuk untuk skema-skema hibah riset yang ditawarkan kementerian RISTEK di tahun-tahun belakangan ini juga terus meningkat. Kedua fenomena tersebut seiring dengan peningkatan jumlah makalah yang masuk ke meja redaksi jurnal ini. Yang menggembirakan juga adalah para mitra bestari yang terus memberikan kontribusi dan semangat tinggi dalam penerbitan ini. Semoga semua hal di atas menjadi tanda cerahnya pengembangan sains dan teknologi di tanah air.

Salah satu fokus pengembangan teknologi di tanah air adalah teknologi informasi (TI). Tulisan yang masuk ke meja redaksi juga banyak berasal dari ranah ini, sehingga tidak heran jurnal kali ini terbit dengan beberapa makalah yang terkait TI. Sebuah artikel membahas pengembangan *power control* untuk sistem *code division multiple access* (CDMA) untuk mengatasi penurunan unjuk kerja karena efek penundaan umpan balik (*feedback delay*). Artikel kedua berkenaan dengan teknik pemberian tanda air untuk video digital.

Beberapa penelitian di dalam negeri juga memusatkan perhatian pada pengembangan energi alternatif. Peta jalan energi (*energy road map*) yang telah dicanangkan oleh pemerintah beberapa tahun lalu nampaknya masih perlu dukungan yang kuat dari berbagai pihak, termasuk para peneliti, mengingat pencapaian target peta jalan masih sangat jauh dari harapan. Oleh sebab itu, menarik sekali menyimak hasil penelitian dari ITS mengenai produksi lipida dari mikroalga untuk produksi biodiesel. Metoda yang digunakan adalah dengan menekan suplai nitrogen dan menaikkan pasokan karbon dioksida.

Jurnal kali ini juga menyajikan sebuah laporan pengamatan lapangan pada sebuah stasiun penelitian petir milik ITB di gunung Tangkuban Perahu. Penelitian tersebut ditujukan untuk mengamati pengaruh induksi dan konduksi gelombang elektromagnetik pada jaringan tegangan rendah yang mengakibatkan kerusakan peralatan elektronik.

Kekayaan alam Indonesia mewujudkan pada keanekaragaman material yang melimpah. Perpaduan *clay montmorillonit* dengan teknologi nano polipropilena, misalnya, dapat dipersembahkan untuk menciptakan bahan yang bermanfaat untuk kemasan makanan. Pengujian pada penelitian ini bertujuan untuk mengetahui stabilitas termal dari material baru tersebut.

Selamat membaca.

- Improved Predictive Power Control of CDMA System in Rayleigh Fading Channel** 1  
*Adit Kurniawan, Iskandar, and Sayid Machdar*
- Kinerja Skema Pemberian Tanda Air Video Digital Berbasis DWT-SVD dengan Detektor Semi-Blind** 7  
*T. Basaruddin dan Della Maulidiya*
- Penerapan Kamera Web Sebagai Pendeteksi Gerakan dengan Antarmuka Directshow** 15  
*Yonatan Santoso, Iwan Setiyawan, dan Victor N. Papilaya*
- Stabilitas Termal Galeri Clay pada Komposit Nano Polipropilena-Clay Montmorillonit dengan Pengkompatibel Polipropilena-g-Maleik Anhidrida** 19  
*Sotya Astutiningsih, Pandu Lanang Kinasih, dan Arief Cahyo Wibowo*
- Induksi dan Konduksi Gelombang Elektromagnetik Akibat Sambaran Petir pada Jaringan Tegangan Rendah** 25  
*Reynaldo Zoro*
- Environmental Remediation Full-Scale Implementation: Back To Simple Microbial Massive Culture Approaches** 33  
*Agung Dhamar Syakti and Mohamad Yani*
- Penetapan Rute dan Perhitungan Keekonomian Pipa Transmisi Gas Muara Bekasi - Muara Tawar Melalui Jalur Lepas Pantai** 37  
*Asep Handaya Saputra dan Ardiansyah*
- Pembuatan Nanopartikel Emas Radioaktif dengan Aktivasi Neutron** 42  
*Rohadi Awaludin*
- Lipid Production from Microalgae *Chlorella vulgaris* as a Promising Candidate for Biodiesel Production** 47  
*Arief Widjaja*

## ENVIRONMENTAL REMEDIATION FULL-SCALE IMPLEMENTATION: BACK TO SIMPLE MICROBIAL MASSIVE CULTURE APPROACHES

Agung Dhamar Syakti<sup>1,2\*)</sup> and Mohamad Yani<sup>2</sup>

1. Fisheries and Marine Sciences Department, Jenderal Soedirman University,  
Karangwangkal, Purwokerto 53123, Indonesia

2. Biotechnology Division, Center for Coastal and Marine Resources Studies, Bogor Agricultural Institute,  
Baranang Siang, Bogor 16144, Indonesia

<sup>\*)</sup>E-mail: agungsyakti@chemist.com

---

### Abstract

Using bioaugmentation and biostimulation approach for contaminated soil bioremediation were investigated and implemented on field scale. We combine those approaches by culturing massively the petrophilic indigenous microorganisms from chronically contaminated soil enriched by mixed manure. Through these methods, bioremediation performance revealed promising results in removing the petroleum hydrocarbons comparatively using metabolite by product such as biosurfactant, specific enzymes and other extra-cellular product which are considered as a difficult task and will impact on cost increase.

*Keywords: Bioremediation, environmental biotechnology, oil and gas industry*

---

### 1. Introduction

Since early 1990s, waste biotreatment that contains the group of compounds known as petroleum hydrocarbons has been developed in Indonesia [1,2]. The negative effects of these compounds are well documented in terms of personal health and that of the environment. Bioremediation technology has enjoyed a growth in popularity over recent years, not least because it is the 'greenest' option for petrochemical waste disposal. Unlike chemical treatments, which produce their own waste bi-products, a bio-treatment involves microbes that simply die off once processing is complete. In addition to this, it requires a modest capital investment and low level energy input, is self sustaining and environmentally safe [3]. This paper describe over the time improvement basing on five platforms technology which have been commensurate for bioremediation research and development. To shed some light, we provided the highlighted of several full-scale implementation of the bioremediation conducted by our institutions.

### 2. Methode

#### Platforms Technology

**Bioremediation agent.** Bioremediation is the technology that utilizes the metabolic potential of microorganisms to clean up contaminated environment.

This technologies share the advantages of *in situ* application and environmental acceptability compared with most physicochemical strategies. In this paper, we focus on bioremediation rather than other biological remediation techniques such as phytoremediation. Current targets include petroleum hydrocarbons products, especially for hazardous crude oil compounds such as BTEX (Benzene, Toluene, Ethylene dan Xylene) and PAHs (Polycyclic Aromatic Hydrocarbons). The technology enables detoxification of environmental areas where the bioremediatory organism is administered with a supplementary source of nutrients [4].

**Bioproducts.** Extra-cellular microbial product have been shown to play key roles in optimization into the overall clean-up process a contaminated sites leading to cleaner, faster, cheaper by bioremediation efforts. By nowadays, we develop an *in situ* exploration and exploitation potential resources from many vulnerable ecosystem, notably for many microbial strains capable to reduce recalcitrant from petroleum hydrocarbons. We consider a deeper understanding of the regulation microbial extracellular production, fundamental relationship between biosurfactant, contaminant solubilization and biodegradation rates as our pillars strategy in integrated waste management technology.

**Metabolic pathways for pollutants decomposition.** Petroleum is a complex mixture of hydrocarbons, but it can be fractionated into aliphatics, aromatics, asphaltics and small portion of non-hydrocarbons compounds [5]. The general outline of bioremediation pathways for aliphatic and aromatic hydrocarbons have been formulated and continues to be developed in greater detail with time. Best practice of such concept was implemented by alternate aerobic-anaerobic modes, depend on the nature of the substances.

**Chemical dispersant agent.** We develop the application of the chemical dispersant agent, a surfactant-based compound in order to accelerate petroleum hydrocarbons degradation and other pollutants and facilitate their mineralization by forming more labile organic compound through the breakdown of intra-molecular bonds. Our current application related to this section is to improve chemically, stabilization and/or solidification processes of pollutants prior to disposal in an off-site landfill.

**Physical agent.** Contaminant bioavailability to microorganisms is affected by sorption/desorption and also by grain size on the soils/sediments. That sorptive properties of soils greatly influence the kinetic behavior of their indigenous microbial communities. Other studies on some physical parameters (e.g. cation, porosity, hydraulic conductivity, and grain size) were performed on representative soil/sediment samples to identify and quantify other parameters affecting in situ bioremediation of the soil/sediment.

### 3. Results and Discussion

#### Environmental Biotechnology Products

Based on the five platforms used as a technology development, from several treatability test on the laboratory, we can therefore group our biotechnological products as follows:

**Bacterial strains cultures.** Conducted research was made in order to isolate a maximum (cultivable and viable cells) strain potentially capable to degrade petroleum hydrocarbon compounds and then to stimulate their biosurfactant production. Some PAHs were used as model organic contaminants to study the effects of petroleum hydrocarbons on marine sedimentary bacterial compartment. The culture strains are then sublimized with the following PAHs: Phenothiazine, Fluorene, Fluoranthene, Dibenzothiophene, Phenanthrene and Pyrene. Overall, our consortia collection was originally isolated from chronically contaminated marine sediment, from crude oil contaminated soil (COCS), mud pit (MP), and compost's material. For instance, from a mangrove's sediment chronically contaminated by petroleum hydrocarbons, 16 different colonies have been isolated and then *Flexibacteraceae bacterium*,

*Bacillus aquimaris*, *B. megaterium*, *B. pumilis*, *Halobacillus trueperi* and *Rhodobacteraceae bacterium* have been identified through 16S DNA amplification using primer 9F and 1510R [6].

**Bioproduct (Metabolite by product).** Metabolites by product of the microbial consortia culture was obtained and separated as a biological product containing surfactant and other unidentified presence of extra cellular product. They simply act as catalysts resulting in the acceleration of the rate of chemical reactions. Reference [7] reported that hydrocarbons have a low solubility in seawater but their bioavailability can be increased by the extra cellular metabolite product (i.e. exopolysaccharides; surfactant) that would be produced by microorganisms. Since bacterial growth required a direct contact of cells with a soluble and/or non-soluble substrate, stimulation by using chemical or biological dispersant (emulsifier, surfactant) will increase degradation rate for many petroleum hydrocarbon compounds such as paraffin [8]; Polycyclic Aromatic Hydrocarbons [9]; crude oil [10,11]. Reference [12] showed high capacity of microbial adhesion to a hydrophobic substrate. We suggest some specific enzymes have been induced and released into liquid media system. Our isolated bacteria may produce their own specific enzymes in order to facilitate the uptake of their sources of carbon and energy. So, by combining the proper bacteria strains with the appropriate bioproduct, mixed formula have an immediate action simultaneously.

Advantages: 1) Applicable for oil contaminant/spills (in case of Marine Oil Spillage) on site; 2) Remediation of remote areas where mobilization of traditional equipment is not possible.

**Surfactant (Chemicals agent).** We develop a methodology which consists a mixture of chemical substance specifically designed to assist in the resolution of emulsions. Such mixture has proven efficacy in resolving oil in water emulsions and inverse emulsions.

The application of such mixture is highly effective in a variety of oil/water/solids. The mixture can help produce high clarity water, a dense rag layer and a clean, high quality oil phase. The mixture compounds are usually slug fed neat to a point of good mixing in the application.

Advantages: To reduce surface and interfacial tension, the mixture works by destabilizing oil-water or water-oil emulsion and then to precipitate oil compounds into organic phase (separation)

**Full-Scale Implementation of the Bioremediation.** The main objective of a full-scale bioremediation

process is to modify environmental conditions so that specific targeted contaminants are converted to those of lesser environmental concern at acceptable rate and cost.

Obviously, such technology is used by enhancing microbial activity in hydrocarbon-contaminated soil by maintaining certain parameters at optimum conditions. Those parameters include nutrients availability, oxygen levels, moisture content, pH, conductivity, temperature, absence of toxic or inhibitory substances as well as the presence of a consortium of microbes capable of affecting the desired conversion [3].

**Unocal Indonesia (1999-2003).** Two consecutive project collaboration with UNOCAL and Bogor Agricultural University have been done. Two projects respectively are (1). Hydrocarbons degradation with bioremediation technology sludge hydrocarbon at UNOCAL Santan Terminal Indonesia and (2). Integrated waste management for hydrocarbons sludge at Santan Terminal, UNOCAL Company Indonesia. Both project have done a good performance since TPH and some heavy metal clean-up has been achieved through bioremediation process. When the project is held, landfarming and static biopile were used in application.

The initial TPH concentration was 15-35 % and following the process (55 to 90 days), the TPH concentration was decrease significantly to less than 2000 ppm. Biodegradation its self has been the major factor eliminating TPH. For this purpose, we have to improve certain environmental conditions such as soil texture, salinity, pH, temperature, moisture, nutrients and oxygen availability. All these environmental conditions can be manipulated relatively easily so that they are no longer limiting for bioremediation but enhance the degradation rate of the target contaminants.

During this task, we simply maintain the optimal growth condition for indigenous microorganisms without any complementari use of the Bioproduct or chemical agent to remediate the soil.

**Brunei Shell Petroleum (2002-2006).** Slope and Sludge tank cleaning for hydrocarbons sludge at Seria Crude Oil Terminal (2002-2006) is another bioremediation implementation project. By this time, we engaged to use slurry-phase treatment by using Bioreactor. Upon completion of the 4-6 processing bioreactor, about 8,000 m<sup>3</sup> of oil sludge was loaded on and spread out. By this project, we use for the first time what we call. About 150 m<sup>3</sup> of *Bioenzymes 2003 1-30*, *SludgeBbreaker* and *Bonia* were added to improve the rate of biodegradation. The results was promoter, within 30 days 150.000 ppm of TPH can be removed to becoming less than 10.000 ppm. Does the bioproducts

effectively work? Simple dilution has been made? This forum will shed some light. Infact, the availability of major nutrients, nitrogen and phosphorus were monitored and measured to assure their availability for the microbial growth.

**Brunei Liquid Natural Gas (2004-2006).** Bioremediation process for other type of waste: Oxazolidone. This compound is the byproduct of a washing process that use sulfonil to rid natural gas of carbon dioxide. With the similar process (bioreactor system), we demonstrated the important removal of derivd-oxazolidone whereas Dipa-oxa (74 to 12 %), Dipa (1.2 to 0 %), Sulfolane (4.5 to 0 %), DEA (3-0 %).

**Exxonmobil Oil Indonesia (2006-2007).** 6000 m<sup>3</sup> of oily waste from mud pit has been treated and backfilled into land spread area. Simple methods by culturing hydrocarbonoclastic bacterium consortia massively prior for bioaugmentation of the bioremediation process are used in this project. The extent of Total Petroleum Hydrocarbons was lower than the threshold value administered from the Indonesian Environmental State Agency (KLH). During monitoring program three month after disposal), we observed more than 95 % of landspreading area was covered by the wild life habitats including grass, leguminaseae, shrub, trees and the animals [13].

**Others Project.** By using a combine techniques, through bioaugmentation (addition adaptive microorganisms) and biostimulation (addition of metabolites by products) as well as physico-chemical reaction, anothers bioremediation project have been done by our institutions. For instance, microbial addition and supplier for Landfarming program at Badak Field, Vico Indonesia Company in 2003, Mud drilling bioremediation project at East Kalimantan in collaboration with Baker Hugnes and Total, and several simulating testing from local and regional oil and gas company.

#### 4. Conclusion

Full-scale application of bioremediation technology has proved that, sophisticated treatment by separated treatment by treatment can be successfully utilized to decontaminate soil matrix. For Indonesian scientist, such challenge and opportunities are open in order to improve deployment of this technology. A microbial ecology study at the microcosm level, for instance, can be developed in this field. Specific activities (*i.e.*, photosynthesis, respiration, degradation) identified through microscale geochemistry (microcosms) may be correlated with changes in community structure, helping to define the actual degradation pattern. Nevertheless, base on our experiences, simple technique to maintain optimum growth condition of microbial massive culture

is also prompted potential for reducing oily waste and its process and operational implicities make it attractive for further field application developments.

### Acknowledgment

Authors thank to the Bioremediation Team of the Center for Coastal and Marine Research Studies (CCMRS) – Bogor Agricultural University which contribute to the successful clean-up objectives. CCMRS-IPB acknowledge Mr. Fajar Aribowo (R.I.P) for his great work in initiating and developing bioremediation program in our research center.

### References

- [1] M. Udiharto, Prosiding Pelatihan dan Lokakarya Peranan Bioremediasi dalam Pengelolaan Lingkungan. LIPI, BPPT dan HSF Jerman, Cibinong, 1996, p.24-39.
- [2] A. Nugroho, Bioremediasi Hidrokarbon Minyak Bumi, Graha Ilmu, Jakarta, 2006, p.158.
- [3] Wackett, L. P. and Bruce, N. C. 2000. Environmental biotechnology towards sustainability. *Current Opinion in Biotechnology*, 11: 229–23.
- [4] S-H. Lee, B-I. Oh, J-G. Kim, *Bioresource Technology* 99 (2008) 2578.
- [5] A.D. Syakti, Thèse-Doctorat, Université Paul Cezanne Aix Marseille III, France, 2004.
- [6] A.D. Syakti, M. Yani, N.V. Hidayati, I.M. Sudiana, Prosiding Seminar Nasional PERMI, Unsoed, Purwokerto, 2008: (In Press).
- [7] A.D. Syakti, M. Acquaviva, M. Gilewicz, P. Doumenq, J.C. Bertrand, *Environmental Research* 96/2 (2004) 228.
- [8] G. Giedraitytė, L. Kalėdienė, A. Bubinas, *Ekologija (Vilnius)* 3 (2001) 38.
- [9] R.S. Makkar, K.J. Rockne, *Environmental Toxicology and Chemistry* 22/10 (2003) 2280.
- [10] G. Zhang, Y-T. Wu, X. Qian, Q. Meng, *J. Zhejiang Univ Sci B*. 6/8 (2005) 725-730.
- [11] K. Urum, T. Pekdemir, *Chemosphere* 57 (2004) 1139-1150.
- [12] M. Goutx, M. Acquaviva, J.C. Bertrand, *Marines Ecology Progress Series* 61 (1990) 291.
- [13] S. Radhi, E.T. Putri, N.S. Khanim, A.D. Syakti, M. Yani, *International Technology Petroleum Conference-12084*, Kuala Lumpur, 2008; (In Press).