Spatial variability of soil saturated hydraulic conductivity in paddy field in accordance to subsurface percolation

K. Wijaya¹, T. Nishimura², B. I. Setiawan³ and S. K. Saptomo³

- (1) Agricultural Engineering Study Program, Jenderal Soedirman University, Jl. dr. Soeparno Kampus Karangwangkal Kotak Pos 125, Purwokerto, 53123, Central Java, Indonesia
- (2) Graduate School of Agriculture and Life Sciences, The University of Tokyo, 1-1-1, Yayoi, Bunkyo-ku, Tokyo 113-8657, Japan
- (3) Department of Civil and Environmental Engineering, Bogor Agricultural University, Kampus IPB Darmaga, Bogor, 16680, Indonesia

Received: 23 June 2009 Accepted: 15 November 2009 Published online: 1 December 2009

Abstract

Insufficient puddling with inappropriate implements or imprecise time/intensity may alter saturated water flow in paddy soil spatially or temporary due to change in aggregate size distribution, dry bulk density, saturated hydraulic conductivity, and percolation rate of the soil. In this study, spatial variability of saturated hydraulic conductivity (K_s), a key parameter of the saturated water flow, in Fuchu Honmachi paddy plot ($100 \text{ m} \times 28 \text{ m}$) was characterized based on dielectric or ADR dry bulk density ($\rho_{b\text{-ADR}}$) with help of non-similar media concept (NSMC) and geostatistics model to meet its correlation to subsurface percolation. A 100 cc core and an ADR data were sampled from each sub-plot ($7 \text{ m} \times 7.5 \text{ m}$), and then were used for measuring and predicting ρ_b and K_s . The predicted data agreed with the measured ones, in which they fitted well the x = y line with RMSE of 0.029 cm^3 cm⁻³ ($R^2 = 0.68$), 0.027 g cm^{-3} ($R^2 = 0.71$) (ρ_b), and 0.098 cm d^{-1} ($R^2 = 0.45$) for θ , ρ_b , and K_s , respectively. The predicted ρ_b and K_s had similar trend in spatial variability to the measured ones particularly within the distance of 46.3-51.9 m and 26.2-27.9 m, respectively. The spatial variability of the predicted K_s coincided to that of the subsurface percolation rate, in which they had similar distance of dependence. The results indicated that the presenting method can be reasonably accepted.

Keywords Spatial variability - Saturated hydraulic conductivity - Paddy field - Dielectric dry bulk density - Subsurface percolation